

AAAI Report 1215 AAAI Project 88018

# QUARTERLY NOISE MONITORING AT BURBANK AIRPORT FOURTH QUARTER 1998

Jane M. Beckmann Farshad Farhang

February 1999

Prepared for:



AAAI Report 1215 AAAI Project 88018

QUARTERLY NOISE MONITORING AT BURBANK AIRPORT FOURTH QUARTER 1998

Jane M. Beckmann Farshad Farhang

FEBRUARY 1999

Prepared for:

Burbank-Glendale-Pasadena Airport Authority 2627 Hollywood Way Burbank, CA 91505

Prepared by:

Acoustical Analysis Associates, Inc. 22148 Sherman Way, Suite 206 Canoga Park, CA 91303

# TABLE OF CONTENTS

Sect	<u>rion</u> Pa	<u>g</u>
I.	INTRODUCTION	1
II.	NOISE MEASUREMENTS	4.
III.	MEASURED NOISE DATA	6
IV.	SCHEDULED AIRLINE AND COMMUTER OPERATIONS	6
V.	CNEL CONTOUR DEVELOPMENT	6
VI.	INCOMPATIBLE LAND USE:	18
REFE	RENCES	20
APPE	NDIX A - NOISE MONITOR INSTRUMENTATION	
APPEI	NDIX B - CALIBRATION LIST OF TABLES	
<u>Table</u>	<u>Pac</u>	је
1.	CNEL VALUES FOR OCTOBER 1998	8
2.	CNEL VALUES FOR NOVEMBER 1998	9
3.	CNEL VALUES FOR DECEMBER 1998	L O
4.	AVERAGE CNEL VALUES	.1
5	WEEKLY SCHEDILED AIR CARRIER AND COMMITTER FLIGHTS 1	2

# LIST OF FIGURES

<u>Figur</u>	<u>re</u>	<u>P</u>	<u>aqe</u>
1.	CNEL 70 CONTOUR FOR BURBANK AIRPORT - FOURTH QUARTER 1998		2
2.	CNEL 65 CONTOUR FOR BURBANK AIRPORT - FOURTH QUARTER 1998	•	3
3.	NOISE MONITOR LOCATIONS	•	5
	LAND USE AREAS INSIDE 65 AND 70 dB CNEL CONTOURS - FOURTH QUARTER 1998		19

# QUARTERLY NOISE MONITORING AT BURBANK AIRPORT FOURTH QUARTER 1998


#### I. INTRODUCTION


In compliance with the California Noise Standards (Reference 1) and the current variance from certain provisions of the Standards (Reference 2), the operator of the Burbank Airport is required to perform noise monitoring in the vicinity of the airport for the purpose of establishing a noise impact boundary. The Noise Standards currently specify a community noise equivalent level (CNEL) of 65 dB for the noise impact boundary. The airport is required to provide, each quarter, an updated annual noise impact contour based on measurement data over the four preceding quarters.

A permanent noise monitoring system became operational in April 1980 and, with brief interruption for system expansion, maintenance, and program changes, has been operational since that time. The original noise monitor sites have remained unchanged (with the exception of Site 8 that was moved about 15 feet because of construction). Two sites were added east of the airport in late 1980. Four sites were added south of the airport in January 1986 in response to the requirement to determine the Three more locations were added in February 1997. 65 dB contour. Two of these, identified as 16 and 17, are south of the airport, and one, 18, is to the west. The site to the west replaces These locations were added to permit monitoring closer Site 8. to the 65 dB contour. The noise monitoring computer at the airport was replaced in August 1995.

This report describes the data acquired by the monitoring system during the Fourth quarter of 1998. Noise impact boundaries for

<sup>&</sup>lt;sup>1</sup> Prior to January 1, 1986, a CNEL of 70 dB defined the noise impact boundary.





65 dB and 70 dB are shown based on these measurements and measurements obtained during the first, second and third quarter of 1998 reported in References 3, 4 and 5. Figure 1 shows the 70 dB contour and Figure 2 shows the 65 dB contour, based on the measured noise data.

#### II. NOISE MEASUREMENTS

#### A. <u>Sites</u>


Aircraft noise levels were monitored at 15 locations prior to February, 1997. Two sites were added in February 1997, and equipment at one site west of the airport was moved to a new location. The noise monitor sites are shown in Figure 3. No data were recorded at Site 8 after Site 18 became active. The site is still shown on this figure.

### B. Noise Measurement Equipment

Each of the microphone locations uses an identical set of equipment connected to a central control unit. The noise level at each site is digitized and transmitted by phone line to the central site. The computer at the central site processes the data to produce (among other measures) the CNEL at each site. Appendix A provides a brief description of the system.

#### C. Noise Data

Electrical power and phone line interruptions occurred several times during the quarter resulting in loss of data. Tables 1, 2, and 3 show each site monitoring RMS "OFF" if the site was operating for less than 94% of the time. The data for these days were excluded from the averages.



#### D. Operational Data

Detailed departure and arrival logs are provided by the airlines. Operations of other jet aircraft are determined from air traffic strips provided by the FAA at Burbank Tower. In addition, flight schedules and logs of nighttime operations are provided by airport personnel.

#### III. MEASURED NOISE DATA

Daily CNEL values for the noise monitoring system are listed in Tables 1, 2, and 3. Table 4 lists the average values for each quarter together with the annual average.

#### IV. SCHEDULED AIRLINE AND COMMUTER OPERATIONS

The scheduled air carrier and commuter operations for the quarter are shown in Table 5.

#### V. CNEL CONTOUR DEVELOPMENT

The contours shown in Figures 1 and 2 are based upon computergenerated "master" contours which are adjusted to reflect the
monitoring data. This fourth quarter 1998 used the master
contours produced by Version 5.1 of the Integrated Noise Model
(INM), a sophisticated aircraft noise modeling program developed
for the Federal Aviation Administration. Inputs to the program
consist of aircraft types and performance data, flight paths,
numbers of operations, and day/evening/night distribution of
flights. The program calculates CNEL values at equally spaced
grid points and produces CNEL contour lines at 1 dB intervals.
The annual average CNEL values at each site were marked at the
appropriate locations on the contour map and the locations of the
65 and 70 dB CNEL contours were determined in the vicinity of
each measuring point. These points were then joined following
the general shape of the computed contours.

The master contours, used in developing the contours for this quarter are based on operations for the 12-month period from January 1995 through December 1995.

TABLE 1. CNEL VALUES FOR OCTOBER 1998

RMS NUMBER

DATE	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18
10/01/98	 69.6	63.6	64.4	64.0	62.7	63.6	 58.1	0.0	 65.0	61.6	 59.0	 56.8	 64.1	61.1	 65.4	66.3	65.6	67.6
10/02/98	69.1	64.3	64.6	62.9	65.3	66.2	59.1	0.0	65.9	59.5	53.2	56.9	64.4	61.8	65.2	66.5	65.1	66.7
10/03/98	66.5	61.5	61.6	59.2	62.0	59.2	58.2	0.0	64.0	58.2	54.8	55.0	60.6	58.3	66.9	64.1	61.8	66.3
10/04/98	67.2	64.3	65.9	65.1	66.2	62.9	64.5	0.0	63.5	56.4	51.5	55.6	62.0	61.6	65.2	67.4	65.0	64.4
10/05/98	66.5	62.1	61.9	62.9	64.3	65.7	62.4	0.0	61.4	60.3	59.5	54.9	60.3	59.1	62.1	64.5	61.6	64.5
10/06/98	67.7	62.0	62.6	62.1	63.3	63.9	62.2	0.0	60.2	63.0	55.8	55.5	61.7	59.9	62.7	64.5	62.3	65.8
10/07/98	67.8	62.5	62.3	63.2	66.6	66.5	63.3	0.0	60.8	62.3	57.0	58.5	61.7	59.7	64.5	64.5	62.2	63.1
10/08/98	68.1	63.6	63.2	63.7	64.3	63.9	63.6	0.0	61.6	61.8	57.7	56.4	62.7	59.8	63.7	65.1	63.3	63.6
10/09/98	69.3	65.5	66.5	64.3	65.7	.64.9	65.3	0.0	64.0	62.0	60.1	58.4	65.2	62.7	66.7	68.2	66.4	67.3
10/10/98	68.6	64.3	66.7	63.5	64.0	61.6	59.5	0.0	63.0	57.7	53.7	57.9	62.4	61.4	67.3	67.9	66.5	64.5
10/11/98	67.4	63.7	64.7	62.4	63.9	61.9	63.2	0.0	64.1	54.7	49.0	55.7	61.6	61.1	64.9	66.8	64.4	65.1
10/12/98	67.8	61.6	62.4	65.0	64.9	65.7	62.9	0.0	64.4	57.8	54.1	55.8	61.2	58.6	63.1	64.1	63.0	65.8
10/13/98	68.2	62.3	63.0	63.8	64.9	65.3	63.2	0.0	64.4	60.9	58.1	57.1	63.9	62.0	64.7	64.8	65.0	66.6
10/14/98	69.7	63.4	63.5	65.3	65.7	68.0	62.6	0.0	65.0	59.6	55.2	58.8	65.0	60.2	65.2	65.4	65.3	65.5
10/15/98	68.3	64.6	65.6	64.9	66.9	65.9	61.6	0.0	64.4	62.9	58.9	59.4	64.4	62.0	66.3	67.3	66.3	65.3
10/16/98	69.4	65.3	65.9	65.9	66.5	67.7	65.5	0.0	63.7	64.4	60.2	58.9	64.3	62.4	65.4	67.6	65.9	65.8
10/17/98	64.2	59.6	60.7	60.3	61.9	62.9	61.2	0.0	59.5	57.0	54.7	53.5	58.5	56.3	63.0	62.5	63.4	66.1
10/18/98	65.6	62.1	62.7	65.4	66.9	60.0	61.3	0.0	63.2	53.4	53.5	55.0	59.2	58.9	62.9	64.4	62.5	65.4
10/19/98	66.0	61.8	62.0	63.8	64.3	65.3	64.2	0.0	62.6	61.0	58.8	56.4	60.7	58.9	62.7	64.4	62.3	64.1
10/20/98	68.1	62.1	62.3	63.4	65.2	65.7	62.9	0.0	62.1	61.5	59.6	58.3	62.7	60.0	64.1	64.5	63.7	64.2
10/21/98	69.2	62.2	62.9	65.3	64.2	64.5	58.4	0.0	65.5	64.5	57.2	56.6	64.7	60.3	64.2	64.8	65.1	66.4
10/22/98	69.2	63.6	64.0	64.1	65.6	64.3	60.6	0.0	65.1	61.9	58.2	57.3	64.3	60.3	65.5	65.9	65.8	66.6
10/23/98	67.5	64.7	65.0	62.4	63.5	63.5	62.0	0.0	64.1	62.3	60.4	56.6	60.0	61.9	63.8	67.0	63.8	66.2
10/24/98	66.2	62.7	62.7	60.6	64.0	64.8	60.2	0.0	61.2	58.2	57.0	56.1	60.0	59.3	62.2	64.9	62.0	63.4
10/25/98	66.9	59.6	60.6	64.5	67.3	70.5	65.9	0.0	61.6	52.6	52.6	57.7	58.7	59.2	60.6	67.2	59.6	66.0
10/26/98	68.1	63.2	63.6	62.4	63.3	65.1	63.5	0.0	65.0	61.3	56.5	58.0	62.9	60.2	64.6	66.0	64.8	66.6
10/27/98	68.5	64.8	63.9	63.8	65.2	66.4	63.6	0.0	63.6	61.1	57.7	57.5	64.3	61.6	64.7	66.3	64.7	64.7
10/28/98	68.3	64.6	65.7	62.8	64.5	65.6	64.0	0.0	62.8	63.3	59.3	58.0	63.7	61.7	65.7	67.5	65.3	66.7
10/29/98	68.4	63.5	63.9	63.6	64.9	66.4	61.3	0.0	65.2	65.7	58.9	57.2	63.8	60.7	65.6	66.0	65.4	66.2
10/30/98	67.7	64.0	65.1	63.9	65.5	67,4	62.6	0.0	65.0	64.1	59.7	58.4	60.8	61.5	63.9	`67.0	63.5	66.8
10/31/98	68,2	60.6	61.3	61.5	62.3	62.6	60.9	0.0	60.9	57.7	51.5	59.9	62.6	57.4	62.6	63.5	62.4	67.7
AVERAGE	68.0	63.3	63.9	63.7	64.9	65.4	62.6	0.0	63.6	61.3	57.4	57.3	62.7	60.6	64.6	65.9	64.3	65.8
NO./DAYS	31	31	31	31	31	31	31	0	31	31	31	31	31	31	31	31	31	31

NO./DAYS

30 30

TABLE 2. CNEL VALUES FOR NOVEMBER 1998

	RMS NUMBER																	
DATE	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18
,								~~~								,		
11/01/98	69.1	64.2	65.1	65.8	66.2	67.3	63.0	OFF	65.2	56.4	52.3	58.9	63.7	61.2	65.4	67.8	65.3	66.6
11/02/98	68.7	63.0	63.6	63.8	65.7	67.7	63.4	OFF	64.2	58.6	54.3	59.0	63.2	61.1	63.8	65.6	63.8	65.5
11/03/98	68.0	63.1	63.1	65.4	65.8	66.6	62.9	OFF	62.7	62.2	57.7	58.8	62.4	60.6	63.5	65.1	63.8	65.2
11/04/98	70.4	64.5	63.7	67.9	71.4	67.7	65.9	OFF	62.1	63.3	59.2	58.7	64.0	61.4	65.4	66.3	65.5	64.3
11/05/98	67.6	59.7	60.3	67.6	67.8	70.3	65.5	OFF	60.2	61.9	58.7	57.7	59.3	59.5	60.3	67.7	60.5	64.8
11/06/98	68.6	64.0	65.1	63.8	65.2	67.7	62.5	OFF	63.4	62.9	60.4	57.7	62.0	61.7	64.5	67.8	64.2	65.4
11/07/98	65.6	62.0	62.3	59.5	63.3	63.2	58.6	OFF	62.4	59.9	55.9	60.0	60.5	59.4	61.9	64.8	61.7	66.7
11/08/98	68.2	65.2	65.9	59.0	63.1	58.5	51.0	OFF	65.3	59.9	54.2	57.3	62.5	62.1	65.4	68.4	64.9	66.6
11/09/98	67.9	56.7	57.4	68.0	68.8	71.0	65.7	OFF	61.5	58.0	54.6	61.5	58.3	57.2	57.2	65.6	57.0	65.8
11/10/98	68.7	62.1	62.3	64.2	65.3	67.3	64.9	OFF	63.7	61.4	58.6	59.8	64.1	59.8	63.7	64.2	63.9	66.1
11/11/98	68.5	65.1	65.6	66.9	66.5	65.1	61.5	OFF	64.7	60.8	55.9	58.7	64.1	62.2	65.7	67.6	65.3	66.1
11/12/98	67.5	63.5	64.4	67.6	66.7	65.4	63.0	OFF	62.6	62.1	59.4	56.7	62.4	61.2	64.5	66.3	63.7	66.7
11/13/98	68.4	63.9	64.9	65.8	66.5	65.9	62.5	OFF	63.1	62.6	58.1	59.3	62.7	61.3	64.7	67.0	64.3	65.4
11/14/98	66.3	61.0	61.7	63.4	66.8	62.9	60.0	OFF	61.0	59.3	51.9	58.3	59.5	OFF	61.8	63.7	61.7	63.7
11/15/98	67.5	63.4	64.1	63.3	64.5	58.2	52.0	OFF	65.3	60.4	59.5	59.3	61.4	OFF	64.4	65.7	63.9	66.6
11/16/98	68.7	63.2	63.4	63.5	64.9	63.1	57.9	OFF	65.3	61.3	55.5	59.6	64.3	OFF	64.5	65.4	64.5	66.4
11/17/98	69.3	65.3	64.3	66.8	68,8	66.3	63.9	OFF	63.1	63.0	58.8	57.8	64.5	OFF	65.0	67.0	64.4	66.9
11/18/98	69.1	63.0	62.1	65.4	65.4	66.3	63.0	OFF	63.2	62.0	58.1	60.3	63.2	OFF	63.6	64.0	63.5	66.6
11/19/98	67.4	61.7	61.9	65.6	65.8	66.6	62.8	OFF	62.0	60.7	60.6	57.6	60.5	OFF	62.5	63.9	62.4	67.7
11/20/98	68.3	64.0	64.1	67.2	67.9	64.8	62.6	OFF	63.1	65.0	60.5	58.5	61.8	OFF	64.4	66.5	63.7	65.9
11/21/98	64.2	59.8	61.1	61.0	63.6	60.3	60.2	OFF	60.7	56.9	49.9	57.3	58.0	OFF	60.5	63.9	59.6	64.6
11/22/98	66.0	61.6	62.0	63.3	64.7	64.5	61.4	OFF	63.3	59.5	50.1	56.4	61.3	58.3	63.8	63.6	63.6	65.0
11/23/98	67.3	62.8	62.9	63.5	63.4	64.1	62.3	OFF	63.3	60.8	60.7	58.8	62.7	59.9	64.0	65.0	63.8	66.5
11/24/98	69.0	64.6	65.4	65.1	66.2	67.4	64.3	OFF	63.7	63.3	60.1	58.0	63.6	62.2	66.1	66.7	65.6	67.8
11/25/98	67.9	64.1	64.3	65.5	65.9	66,6	62.9	OFF	64.3	62.1	58.2	61.5	62.5	61.2	65.6	65.8	65.3	66.7
11/26/98	63.6	59.2	59.5	59.4	61.0	60.2	57.7	OFF	60.2	58,4	51.5	52.2	59.4	55.3	60.6	61.4	60.3	63.9
11/27/98	67.4	61.1	61.3	62.9	63.8	61.2	57.4	OFF	63.7	60.4	59.0	58.1	62.4	57.9	63.4	63.0	62.6	64.5
11/28/98	70.2	64.2	64.5	66.2	66.2	63.5	59.2	OFF	62.8	63.1	55.5	59.4	62.6	62.4	64.8	66.0	64.6	63.9
11/29/98	68.5	64.7	65.2	60.4	63.2	61.7	55.6	OFF	66.4	55.1	47.0	59.9	64.0	61.8	66.0	67.0	65.6	67.4
11/30/98	69.2	65.3	65.8	63.7	66.9	64.7	62.0	OFF	67.8	61.8	59.8	59.8	66.0	62.1	67.7	67.6	67.7	68.1
AVERAGE	68.1	63.3	63.6	65.0	66.2	65.9	62.3	0.0	63.7	61.3	57.7	58.8	62.6	60.8	64.3	65.9	64.0	66.1

TABLE 3. CNEL VALUES FOR DECEMBER 1998

								RM	IS NUMB	ER -								
DATE	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18
12/01/98	70.0	65.6	65.4	65.7	67.7	68.5	62.4	OFF	66.0	62.3	59.3	60.6	63.5	63.0	65.6	68.4	65.2	67.0
12/02/98	69.1	64.1	64.3	66.2	67.1	66.2	61.0	OFF	66.3	62.7	60.7	59.7	63.6	61.6	65.6	66.4	65.3	67.9
12/03/98	68.8	64.8	64.6	65.7	67.4	66.7	59.7	OFF	66.2	62.0	57.7	58.6	64.4	62.0	66.4	66.6	66.0	68.1
12/04/98	69.1	64.1	63.9	63.6	65.1	65.2	60.8	OFF	64.8	62.8	58.3	59.1	68.1	61.5	64.9	66.1	64.6	66.0
12/05/98	62.9	52.6	52.1	65.1	65.9	68.5	63.1	OFF	57.9	56.1	OFF	55.4	55.1	53.6	54.8	63.4	53.3	61.5
12/06/98	63.1	50.6	51.1	65.8	67.4	69.2	63.6	OFF	63.7	55.6	51.8	57.6	47.6	53.6	42.9	64.0	43.3	66.8
12/07/98	67.0	8.06	60.4	67.7	66.3	65.0	62.6	OFF	61.9	60.8	61.3	59.8	61.9	OFF	62.1	63.3	62.2	64.0
12/08/98	68.7	59.7	58.5	67.7	68.6	70.8	64.8	OFF	58.6	62.3	59.2	63.3	58.2	OFF	58.8	67.9	58.9	63.6
12/09/98	65.3	54.6	54.7	66.4	65.7	69.2	63.9	OFF	60.7	58 <b>.</b> 9	51.8	56.9	54.4	53.9	57.4	61.6	56.9	65.4
12/10/98	68.1	62.0	61.8	65.3	66.0	64.6	60.7	OFF	61.9	60.6	58.8	60.8	60.7	OFF	62.6	64.1	61.7	65.3
12/11/98	69.1	62.4	61.8	64.1	65.5	66.4	62.8	OFF	62.3	63.5	56.6	62.7	61.1	OFF	62.6	63.8	62.4	65.8
12/12/98	63.9	58.1	58.9	60.7	62.6	63.3	57.9	OFF	60.5	59.2	56.6	56.1	56.2	55.0	58.8	61.2	58.5	64.2
12/13/98	68.2	62.1	61.8	65.0	66.1	64.3	62.5	OFF	62.7	59.7	59.4	59.5	59.7	58.1	62.6	63.6	61.8	64.9
12/14/98	64.0	58.6	59.0	65.5	67.2	68.7	63.4	OFF	58.7	60.5	57.0	60.5	57.6	59.1	60.2	67.5	59.6	65.4
12/15/98	65.2	55.4	56.0	66.5	66.9	71.1	64.5	OFF	62.4	61.3	52.2	60.5	55.3	56.6	55.9	63.0	56.7	68.4
12/16/98	OFF	OFF	OFF	OFF	OFF	OFF	OFF	OFF	OFF	OFF	OFF	OFF						
12/17/98	OFF	OFF	OFF	OFF	OFF	OFF	OFF	OFF	OFF	OFF	OFF	OFF						
12/18/98	OFF	OFF	OFF	OFF	OFF	OFF	OFF	OFF	OFF	OFF	OFF	OFF						
12/19/98	67.5	63.1	63.9	63.5	64.9	60.3	54.4	OFF	64.7	59.7	52.6	58.0	62.8	60.3	64.0	65.7	63.5	65.2
12/20/98	66.0	61.6	61.6	60.2	63.8	63.3	58.2	OFF	64.6	57.4	48.9	56.3	60.5	58.0	62.2	63.1	61.2	67.4
12/21/98	66.6	61.7	62.0	62,2	62.0	61.7	61.3	OFF	61.4	60.4	56.6	56.9	61.5	58.1	63.6	64.5	63.0	64.4
12/22/98	67.2	62.3	62.1	64.7	63.7	64.7	63.1	OFF	61.1	62.0	57.9	62.9	61.3	OFF	63.6	64.6	63.2	64.3
12/23/98	67.9	63.5	63.8	69.3	69.2	64.4	62.8	OFF	62.2	62.6	60.3	60.8	61.8	60.2	65.0	66.0	64.2	63.9
12/24/98	65.5	60.4	60.3	65.6	66.2	65.4	61.3	OFF	60.2	62.2	57.3	59.8	57.6	57.0	60.4	63.1	59.8	64.3
12/25/98	61.6	56.9	56.7	59.0	61.0	58.5	54.7	OFF	59.6	58.3	55.6	53.5	55.7	52.7	58.5	59.0	58.1	63.2
12/26/98	64.8	60.9	61.7	64.3	63.7	59.3	59.3	OFF	59.9	60.0	53.4	54.3	59.2	57.8	61.7	63.1	61.9	63.2
12/27/98	67.2	63.1	63.2	65.4	65.6	61.5	61.0	OFF	62.2	54.9	48.4	58.7	63.7	59.9	64.1	64,8	63.6	64.7
12/28/98	66.8	63.4	64.1	67.8	67.3	65.4	62.8	OFF	63.3	59.2	57.1	59.0	60.7	60.2	64.2	65.5	63.6	65.8
12/29/98	68.7	64.0	65.2	69.6	73.7	65.2	61.1	OFF	64.2			62.8						
12/30/98												59.7						
12/31/98												59.5						
, ,												••••				•		
AVERAGE	67.3	61.9	62.0	65.7	66.8	66.5	62.0	0.0	63.0	61.1	57.5	59.7	61.6	59.3	62.9	65.0	62.4	65.9
NO./DAYS	28	28	28	28	28	28	28	0	28	28	27	28	28	23	28	28	28	28
QTR. AVG.	67.8	62.9	63.3	64.9	66.0	65.9	62.3	0.0	63.4	61.2	57.5	58.7	62.4	60.3	64.0	65.7	63.7	65.9
NO./DAYS	89	89	89	89	89	89	89	0	89	89	88	89	89	76	89	89	89	89

TABLE 4. AVERAGE CNEL VALUES

Site No.	1st Quarter 1998	2nd Quarter 1998	3rd Quarter 1998	4th Quarter 1998	4-Quarter Average
1	69.0	68.0	67.4	67.8	68.1
2	63.5	62.9	62.6	62.9	63.0
3	64.0	63.4	63.4	63.3	63.5
4	65.8	63.5	63.0	64.9	64.4
5	66.7	65.0	64.0	66.0	65.5
6	66.9	64.6	64.9	65.9	65.7
7	63.1	61.9	62.8	62.3	62.5
8	0.0	0.0	0.0	0.0	
9	64.1	63.8	63.6	63.4	63.7
10	61.2	60.8	60.9	61.2	61.0
11	57.4	56.9	56.0	57.5	57.0
12	60.0	57.1	55.4	58.7	58.1
13	63.0	62.8	61.8	62.4	62.5
14	61.0	60.2	60.3	60.3	60.5
15	64.7	64.1	63.8	64.0	64.2
16	0.0	0.0	67.3*	65.7	
17	63.9	63.7	63.8	63.7	63.8
18	66.3	65.4	65.5	65.9	65.8

<sup>\*</sup>Only 9 days in the service

TABLE 5. WEEKLY SCHEDULED AIR CARRIER AND COMMUTER FLIGHTS FOR THE FOURTH QUARTER 1998

	AA DEPA MD80	SCHEDU AA ARRI MD80	JLE IN 1 AS DEPA MD80	EFFECT AS ARRI MD80	FROM 10/ HP DEPA B7373	1/98 - HP ARRI B7373	10/24/ WN DEPA B7373	98 WN ARRI B7373
DAY	14	7	28	28	27	27	204	184
EVENING	0	7	6	13	4	7	61	67
NIGHT	0	0	7	0	7	4	0	14
TOTAL	14	14	41	41	38	38	265	265
	WN DEPA B7375	SCHEDU WN ARRI B7375	ULE IN I WN DEPA B7377	EFFECT WN ARRI B7377	FROM 10/ UA DEPA B7373	1/98 - UA ARRI B7373	10/24/ UA DEPA B7375	98 UA ARRI B7375
DAY	83	83	0	0	14	7	75	66
EVENING	0	0	Ō	Ō	0	7	13	20
NIGHT	0	0	0	0	0	0	5	7
TOTAL	83	83	0	0	14	14	93	93
	UA DEPA B757	SCHEDU UA ARRI B757	LE IN E QQ DEPA MD80	EFFECT D QQ ARRI MD80	FROM 10/ QQ DEPA MD90	1/98 - QQ ARRI MD90	10/24/9 COMM DEPA BRASIL	98 COMM ARRI BRASIL
DAY	0	0	13	13	7	7	63	63
EVENING	0	0	0	6	0	0	0	0
NIGHT	0	0	6	0	0	0	0	0
TOTAL	0	0	19	19	7	7	63	63
	UPS DEPA B757	SCHEDU UPS ARRI B757	LE IN E FE DEPA B727Q	FFECT I FE ARRI B727Q	FROM 10/ FE DEPA A300	1/98 - FE ARRI A300	10/24/9 TOTAL DEPA	98 TOTAL ARRI
DAY	. 0	5	0	0	0	5	528	495
EVENING	5	0	0	0	5	0	94	127
NIGHT	0	0	0	0	0	0	25	25
TOTAL	5	5	0	0	5	5	647	647

TABLE 5. (CONTINUED)

	AA DEPA MD80	SCHEDO AA ARRI MD80	ULE IN AS DEPA MD80	EFFECT AS ARRI MD80	FROM 10/ HP DEPA B7373	25/98 HP ARRI B7373	11/17/ WN DEPA B7373	98 WN ARRI B7373
DAY	14	7	21	21	20	20	204	184
EVENING	0	7	6	13	4	7	61	67
NIGHT	0	0	7	0	7	4	0	14
TOTAL	14	14	34	34	31	31	265	265
		<u> </u>						
	E-TR-T	SCHEDU	JLE IN		FROM 10/			
	WN DEPA	WN ARRI	WN DEPA	WN	UA	UA	UA	UA
	B7375	B73.75	B7377	ARRI B7377	DEPA B7373	ARRI	DEPA	ARRI
	5/3/3	בו.כות	B1311	D/3//	D/3/3	B7373	B7375	B7375
DAY	83	83	0	0	14	7	75	66
EVENING	0	0	0	0	0	7	13	20
NIGHT	0	0	0	0	0	0	5	7
TOTAL	83	83	. 0	0	14	14	93	93
	UA	SCHEDU UA	LE IN :	EFFECT 1	FROM 10/	25/98 - QQ	11/17/9 COMM	8 COMM
	DEPA	ARRI	DEPA	ARRI	DEPA	ARRI	DEPA	ARRI
	B757	B757	MD80	MD80	MD90	MD90	BRASIL	
DAY	0	0	1.2					•
EVENING	0	0	13 0	13 6	- 7 0	7 0	63	63
NIGHT	0	0	6	0	0	0	0 0	0 0
TOTAL	Ö	Ö	19	19	7	7	63	63
			-					
		SCHEDU	LE IN E	EFFECT F	FROM 10/2		11/17/9	8
	UPS	UPS	FE .	FE	FE	FE	TOTAL	TOTAL
	DEPA B757	ARRI B757	DEPA B727Q	ARRI B727Q	DEPA A300	ARRI A300	DEPA	ARRI
	2121		5121Q	BIZIQ	AJUU	AJUU		
DAY	0	5	0	0	0	5	514	481
EVENING	5	0	0	0	5	0	94	127
NIGHT	0	0	0	0	0	0	25	25
TOTAL	5	5	0	0	5	5	633	633

TABLE 5. (CONTINUED)

			JLE IN		FROM 11/			98
	AA	AA	AS	AS	HP	HP	WN	WN
	DEPA	ARRI	DEPA	ARRI	DEPA	ARRI	DEPA	ARRI
	MD80	MD80	MD80	MD80	B7373	B7373	B7373	B7373
DAY	14	7	21	21	27	27	204	184
EVENING	0	7	6	13	4	7	61	67
NIGHT	0	0	7	0	7	4	0	14
TOTAL	14	14	34	34	38	38	265	265
		COHEDI	II EI TAY 1		TDOM 11/	10/00		
	WN	WN	MM TR TM 1	WN	FROM 11/			
	DEPA	ARRI	DEPA	ARRI	UA DEPA	UA	UA	UA
	B7375	B7375	B7377	B7377		ARRI	DEPA	ARRI
	כונום	D/3/5	D/3//	B/3//	B7373	B7373	B7375	B7375
DAY	83	83	0	0	14	7	75	66
EVENING	0	0	0	0	0	7	13	20
NIGHT	0	0	0	0	0	0	5	7
TOTAL	83	83	0	0	14	14	93	93
					FROM 11/			98
	UA	UA	QQ	QQ	QQ	QQ	COMM	COMM
	DEPA	ARRI	DEPA	ARRI	DEPA	ARRI	DEPA	ARRI
	B757	B757	MD80	MD80	MD90	MD90	BRASIL	BRASIL
DAY	0	0	13	13	7	7	63	63
EVENING	0	0	0	6	0	0	0	0
NIGHT	0	0	6	0	0	0	0	0
TOTAL	0	0	19	19	7	7	63	63
		COMPAN	* F. * * * *					
	tina				FROM 11/:			
	UPS DEPA	UPS ARRI	FE	FE	FE	FE	TOTAL	TOTAL
	B757	B757	DEPA B727Q	ARRI B727Q	DEPA A300	ARRI A300	DEPA	ARRI
	_ · <i></i> ·	· - ·						
DAY	0	5	0	0	0	5	521	488
EVENING	5	0	0	0	5	0	94	127
NIGHT	0	0	0	0	0	0	25	25
TOTAL	5	5	0	0	5	5	640	640

TABLE 5. (CONTINUED)

	AA DEPA MD80	SCHEDU AA ARRI MD80	JLE IN AS DEPA MD80	EFFECT AS ARRI MD80	FROM 12/ HP DEPA B7373	2/98 - HP ARRI B7373	12/14/ WN DEPA B7373	98 WN ARRI B7373
DAY EVENING NIGHT TOTAL	7 0 0 7	0 7 0 7	21 6 7 34	21 13 0 34	27 4 7 38	27 7 4 38	204 61 0 265	184 67 14 265
	WN DEPA B7375	SCHEDU WN ARRI B7375	LE IN WN DEPA B7377	WN ARRI	FROM 12/ UA DEPA B7373	2/98 - UA ARRI B7373	12/14/ UA DEPA B7375	98 UA ARRI B7375
DAY EVENING NIGHT TOTAL	83 0 0 83	83 0 0 83	0 0 0 0	0. 0 0	14 0 0 14	7 7 0 14	75 13 5 93	66 20 7 93
	UA DEPA B757	SCHEDU UA ARRI B757	LE IN D QQ DEPA MD80	EFFECT : QQ ARRI MD80	FROM 12/ QQ DEPA MD90	2/98 - QQ ARRI MD90	12/14/ COMM DEPA BRASIL	COMM ARRI
DAY EVENING NIGHT TOTAL	0 0 0	0 0 0 0	13 0 6 19	13 6 0 19	7 0 0 7	7 0 0 7	63 0 0 63	63 0 0 63
	UPS DEPA B757	SCHEDU UPS ARRI B757	LE IN I FE DEPA B727Q	EFFECT I FE ARRI B727Q	FROM 12/ FE DEPA A300	2/98 - FE ARRI A300	12/14/9 TOTAL DEPA	8 TOTAL ARRI
DAY EVENING NIGHT TOTAL	0 5 0 5	5 0 0 5	4 0 0 4	0 0 4 4	0 5 0 5	5 0 0 5	518 94 25 637	481 127 29 637

TABLE 5. (CONTINUED)

	AA DEPA MD80	SCHEDU AA ARRI MD80	JLE IN E AS DEPA MD80	EFFECT I AS ARRI MD80	FROM 12/ HP DEPA B7373	15/98 - HP ARRI B7373	WN DEPA B7373	WN ARRI B7373
DAY EVENING NIGHT TOTAL	7 0 0 7	0 7 0 7	21 6 7 34	21 13 0 34	27 4 7 38	27 7 4 38	204 61 0 265	184 67 14 265
	WN DEPA B7375	SCHEDU WN ARRI B7375	ULE IN E WN DEPA B7377	FFECT F WN ARRI B7377	ROM 12/ UA DEPA B7373	15/98 - UA ARRI B7373	UA DEPA B7375	UA ARRI B7375
DAY EVENING NIGHT TOTAL	83 0 0 83	83 0 0 83	0 0 0	0 0 0	34 13 0 47	27 20 0 47	54 0 6 60	48 6 6
DAY EVENING NIGHT TOTAL	UA DEPA B757 0 0 0	SCHEDU UA ARRI B757 0 0 0	LE IN E QQ DEPA MD80 13 0 6	FFECT F QQ ARRI MD80 13 6 0	ROM 12/ QQ DEPA MD90 7 0 0	15/98 - QQ ARRI MD90 7 0 0	COMM DEPA BRASIL 63 0 0	COMM ARRI BRASIL 63 0 0
	UPS DEPA B757	SCHEDU UPS ARRI B757	LE IN E FE DEPA. B727Q	FFECT F FE ARRI B727Q	ROM 12/ FE DEPA A300	15/98 - FE ARRI A300	TOTAL DEPA	TOTAL ARRI
DAY EVENING NIGHT TOTAL	0 5 0 5	5 0 0 5	4 0 0 4	0 0 4 4	0 5 0 5	5 0 0 5	517 94 26 637	483 126 28 637

#### TABLE 5. (CONTINUED)

## FOURTH QUARTER 1998

### PERIOD TOTALS FOR AIR CARRIERS AND COMMUTERS

#### AIR CARRIERS

	DEP	<u>ARR</u>
DAY	6005	5562
EVE	1236	1667
NIGHT	331	343
TOTAL	7572	7572

### COMMUTERS

	DEP	<u>ARR</u>
DAY	828	828
EVE	0	0
NIGHT	0	0
TOTAL	828	828

## AIR CARRIERS AND COMMUTERS

	$\overline{\mathtt{DEP}}$	<u>ARR</u>
DAY	6833	6390
EVE	1236	1667
NIGHT	<u>331</u>	<u>343</u>
TOTAL	8400	8400

#### VI. INCOMPATIBLE LAND USE

The contours shown in Figures 1 and 2 were digitized and overlaid on a digital land use map of the area around the airport<sup>2</sup>. The area enclosed by the contours for incompatible land uses were computed. The incompatible land use area was 344.58 acres within the 65 dB contour and 35.47 acres within the 70 dB contour. It should be noted that these areas do not include the soundproofed schools in the airport vicinity. The soundproofed schools include the Luther Burbank Middle School, St. Patrick, and Glenwood schools. The total areas enclosed by the 65 and 70 dB CNEL contours were 1,249.0 and 506.9 acres, respectively.

The estimated numbers of residences are 1,551 within the 65 dB contour, and 160 within the 70 dB contour. The estimated numbers of people residing within the 65 and 70 dB CNEL contours are 4,140 and 426 respectively. Figure 4 is a graphical depiction of land use areas inside the 65 and 70 dB CNEL contours for fourth quarter 1998.

<sup>&</sup>lt;sup>2</sup> The airport maintains a digitized map of the existing land use around the airport. This data base is employed on a consistent basis in determining the land use and contour areas reported in the quarterly noise reports.




Figure 4. LAND USE AREAS INSIDE 65 AND 70 dB CNEL CONTOURS - FOURTH QUARTER 1998

#### REFERENCES

- 1. California Department of Transportation, Division of Aeronautics, "Noise Standards", California Code of Regulations, Title 21, Chapter 2.5, Subchapter 6.
- 2. L-30488, Department of Transportation, State of California, 27 June 1984.
- 3. "Quarterly Noise Monitoring at Burbank Airport, First Quarter 1998", AAAI Report 1212.
- 4. "Quarterly Noise Monitoring at Burbank Airport, second Quarter 1998", AAAI Report 1213
- 5. "Quarterly Noise Monitoring at Burbank Airport, third Quarter 1998", AAAI Report 1214

APPENDIX A
NOISE MONITOR INSTRUMENTATION

# APPENDIX A NOISE MONITOR INSTRUMENTATION

The permanent noise monitor system, manufactured by Tracor, consists of 17 remote monitoring stations (RMS) connected to a central site by telephone lines. The system block diagram showing the major elements is shown in Figure A-1. The electrical signal generated by the microphone/preamplifier assembly at each site is processed in the RMS electronics. The signal is passed through an A-weighting filter and is then detected and converted to a digital level signal in decibels with a resolution of 0.1 dB.

The digitized sound level is transmitted every half second by telephone line to the central site. The data received by the central site are processed by the computer. According to preset parameters, the noise is separated into two categories--aircraft noise and community noise. Each event attributed to an aircraft is saved in a noise event file. Computations are made of hourly noise level, community noise equivalent level, runway use, and other parameters. A wide variety of data presentations is available by exercising a number of routines provided by Tracor, as well as special-purpose routines that can be generated by the user.

The locations of the remote sites (shown in Figure 3) are listed relative to the runway thresholds in Table A-1.




FIGURE A-1. PERMANENT NOISE MONITOR SYSTEM BLOCK DIAGRAM

TABLE A-1 NOISE MONITOR SITE LOCATIONS

	Distance From	Distance From
Site No.	N. End of RW 15	Extended Centerline
1	8590	-1490
2	10830	1590
3	13440	-1090
4	-150	-1200
5	-810	1100
6	-3280	-740
7	-4720	-50
12	7520	-3220
13	10660	-3600
. 14	12780	1160
15	13380	-3920
16	11600	360
17	12900	-3520

Note: Positive distances from the runway threshold are to the south; positive distances from the extended centerline are to the east.

	Distance From	Distance From	
Site No.	W. End of RW 8	Extended Centerline	
8	· -5900	-820	
9	-8700	220	
10	8180	-800	
11"	8740	-110	
18	-5880	-440	

Note: Positive distances from the runway threshold are to the east; positive distances from the extended centerline are to the north.

APPENDIX B CALIBRATION

# APPENDIX B

The system was calibrated during setup using a Bruel and Kjaer pistonphone. Acoustic calibrations are being performed approximately every six months. Electrical calibrations are performed automatically shortly after midnight each day. Figure B-1 shows the latest calibration certificate of the pistonphone employed in the acoustic calibrations and Figure B-2 shows a typical electrical calibration.

# ACOUSTICAL ANALYSIS ASSOCIATES, INC.

22148 SHERMAN WAY, SUITE 206, CANOGA PARK, CA 91303 - (818) 713-1160

# CERTIFICATE OF CALIBRATION

#### **PISTONPHONE TYPE 4220**

The calibration	n is p	erforn	ned by	compar	lson v	with
Pistonphone	Type 4	1220,	Serial i	0 کی ۵۰	250	<u>á</u> .

Calibrated by: ODIN Date: 16 Jul 19 98

If the Ambient Presssure P<sub>a</sub> deviates from the above stated nominal value 1013 mbar a correction SPL should be added to the calibrated Sound Pressure Level.

 $SPL = 20 \times Log_{10} \frac{P_a (mbar)}{1013}$ 

Calibrated By: R.P. Costello

Date: 2 Jan , 19 99

R. Peter Costello Acoustical Analysis Associates, Inc. 22148 Sherman Way, Suite 206 Canoga Park, CA 91303 (818) 713-1160 Serial No.: 757164

Sound Pressure Level produced in the coupler terminated by a loading volume of 1,333 cm<sup>3</sup> at 1013 mbar, 20°C, 65% R.H.

<u>/23.90</u> dB re. 20µРа

Frequency: 250.7 Hz ± 0,5 Hz in "On" position.

Distortion: Less than 3%

Condition of Test:

Ambient Pressure: 990 mbar
Temperature: 24 °C
Relative Humidity: 30 %

# INSTRUMENTATION USED FOR CALIBRATION

ITEM	TYPE	SERIAL NO.	CAL DATE	CAL BY	DUE DATE
MEASURING AMP B.F.OSCILLATOR SINE GENERATOR PISTONPHONE PISTONPHONE MICROPHONE * MICROPHONE *	2606 1022 1023 4220 4220 4161 4144	586767 466495 553662 80256 893686 559578 535815	16 SEP 98 9 MAR 98 16 SEP 98 16 JUL 98 11 MAR 98 23 SEP 98 23 SEP 98	ODIN ODIN ODIN ODIN ODIN ODIN	16 SEP 99 9 MAR 99 16 SEP 99 16 JUL 99 11 MAR 99 23 SEP 99 23 SEP 99

\*B&K ADAPTERS DB0111 AND DD0015 USED TO SIMULATE WE640AA MICROPHONE.

```
Calibration Report
******
Calibration RMS: 1
                    Passed Peak:110.0 dB @ 11/10/1995
                                                       0:06
Calibration
            RMS: 2
                    Passed Peak:110.1 dB @ 11/10/1995
                                                       0:06
Calibration RMS: 3
                    Passed Peak:109.8 dB @ 11/10/1995
                                                       0:06
Calibration RMS: 4
                    Passed Peak:110.0 dB @ 11/10/1995
                                                       0:06
Calibration
                    Passed Peak:110.1 dB @ 11/10/1995
            RMS: 5
                                                       0:06
            RMS: 6
Calibration
                    Passed Peak:110.0 dB @ 11/10/1995
                                                       0:06
Calibration
            RMS: 7
                    Passed Peak:110.0 dB @ 11/10/1995
                                                       0:06
Calibration
            RMS: 8
                    Passed Peak:110.0 dB @ 11/10/1995
                                                       0:06
Calibration RMS: 9 Passed Peak:109.9 dB @ 11/10/1995
                                                       0:06
Calibration
            RMS:10
                    Passed Peak:110.0 dB @ 11/10/1995
                                                       0:06
Calibration
            RMS:11
                    Passed Peak:109.9 dB @ 11/10/1995
                                                       0:06
Calibration
            RMS:12
                    Passed Peak:110.0 dB @ 11/10/1995
                                                       0:06
Calibration
                    Passed Peak:110.0 dB @ 11/10/1995
            RMS:13
                                                      0:06
Calibration
            RMS:14
                    Passed Peak:109.9 dB @ 11/10/1995
                                                      0:06
Calibration RMS:15 Passed Peak:110.0 dB @ 11/10/1995
                                                      0:06
```

Figure B-2. Typical Daily Electrical Calibration